



STYLE  
7200R / 7250R

RESIDENTIAL

7200R - BLACKOUT FABRIC  
7250R - LIGHT-FILTERING FABRIC

---

WEAVING  
EXCELLENCE  
WITH  
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
<b>STYLE 7200R - BLACKOUT</b>							
RB1	Swan	0	71	29	0	0.23	0.19
RB8	Raven	0	70	30	0	0.23	0.20



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorptance  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at [www.phifer.com](http://www.phifer.com).



STYLE  
7200R

RB1  
**Swan**

RB2  
**Oyster**

RB3  
**Sail**

RB4  
**Chiffon**

RB6  
**Earl Grey**

RB5  
**Chrome**

RB7  
**Blazer**

RB8  
**Raven**



STYLE  
7250R

RL1  
**Swan**

RL2  
**Oyster**

RL3  
**Sail**

RL4  
**Chiffon**

RL6  
**Earl Grey**

RL5  
**Chrome**

RL7  
**Blazer**

RL8  
**Raven**

# STYLE 7200R / 7250R SPECIFICATIONS

Whether contemporary or traditional, Style 7200R complements any design scheme, combining total light blockage with a neutral yet subtly variegated pattern. Style 7250R offers a light-filtering option, using the same face fabric and pattern of Style 7200R to allow natural light to brighten interior spaces.

These fabrics are suitable for roller shades, Roman shades and panel track systems and are ideal for residential use.

**STYLE 7200R FIRE CLASSIFICATION** California Technical Bulletin 117 IBC Section 803.1.1 (Class B Rating)  
NFPA 101 (Class B Rating)

**STYLE 7250R FIRE CLASSIFICATION** California Technical Bulletin 117 IBC Section 803.1.1 (Class A Rating)  
NFPA 101 (Class A Rating)

*Fire classifications are subject to change. Please go to [phifer.com](http://phifer.com) for the most current information.*

**BACTERIA AND FUNGAL RESISTANCE** ASTM G21-96 AATCC 174-1998 Part II and III

**ENVIRONMENTAL CERTIFICATION** GREENGUARD GREENGUARD Gold  
Certified to these standards for low chemical emissions into indoor air during product usage

**SAFE USE** RoHS/Directive 2002/95/EC  
ANSI/WCMA A 100.1-2007 for lead content  
US Consumer Product Safety Commission Section 101

**WARRANTY** 5-year interior

**UV PROTECTION** Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

**CLEANING INSTRUCTIONS** Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

*Railroading this fabric is not recommended.*

*Colors may vary slightly from swatch samples. All variations are within industry standards.*

STYLE	7200R	7250R
<b>WIDTHS</b>	118" 300 cm	118" 300 cm
<b>ROLL LENGTH</b>	22 Linear Yards 20 Linear Meters	22 Linear Yards 20 Linear Meters
<b>COMPOSITION</b>	100% Polyester with Acrylic Foamed Backing	100% Polyester with Acrylic Coating
<b>MESH WEIGHT</b>	11.06 oz/yd <sup>2</sup> 375 g/m <sup>2</sup>	6.19 oz/yd <sup>2</sup> 210 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.024 in 0.60 mm	0.018 in 0.45 mm
<b>OPENNESS FACTOR</b>	Opaque	Light-filtering

**PHIFER**  
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403 -1700 USA  
Phone: 205.345.2120 • FAX: 205.391.0799  
Toll Free USA/Canada: 1.800.221.5497  
[phifer.com](http://phifer.com) • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
™ UL, the UL logos and the UL mark are trademarks of UL LLC.  
Photo courtesy of Hunter Douglas, South America.  
© PHIFER INCORPORATED V20 021420 3038201