



STYLE
7600 / 7650

7600 - BLACKOUT FABRIC
7650 - LIGHT-FILTERING FABRIC

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 7600 - BLACKOUT							
U90	Bright White	0	46	54	0	0.37	0.26
U97	Coal	0	46	54	0	0.37	0.26



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



MIF Seal of Approval



STYLE 7600



STYLE 7650

TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at phifer.com.



STYLE
7600

U90
Bright White

U99
Ivory

U91
Shell

U92
Khaki

U93
Dove Grey

U94
Taupe

U95
Thunder

U96
Coffee

U97
Coal



STYLE
7650

U90
Bright White

U99
Ivory

U91
Shell

U92
Khaki

U93
Dove Grey

U94
Taupe

U95
Thunder

U96
Coffee

U97
Coal

STYLE 7600/ 7650 SPECIFICATIONS

With a classic linen pattern face and soft PVC-free backing, Style 7600 combines total light blockage with timeless design. As a light-filtering option, Style 7650 uses the same linen pattern as Style 7600 while allowing filtered natural light to permeate your interior space. These fabrics are suitable for roller shades, Roman shades and panel track systems.

FIRE CLASSIFICATION	California U.S. Title 19 (small scale)	NFPA 701 TM#1 (small scale)
	BS 5867 Part 2 Type B Performance	CAN/ULC-S 109 (large and small scale)
<i>Fire classifications are subject to change. Please go to phifer.com for the most current information.</i>		
BACTERIA AND FUNGAL RESISTANCE	ASTM G21-96	ASTM E 2180
ENVIRONMENTAL CERTIFICATION	GREENGUARD	GREENGUARD Gold
	Certified to these standards for low chemical emissions into indoor air during product usage	
SAFE USE	RoHS/Directive 2002/95/EC	
	ANSI/WCMA A 100.1-2007 for lead content	
	US Consumer Product Safety Commission Section 101	
WARRANTY	5-year interior	
ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with	
	ASTM C423-09a	
UV PROTECTION	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes	
CLEANING INSTRUCTIONS	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.	
	<i>Railroading this fabric is not recommended. Colors may vary slightly from swatch samples. All variations are within industry standards.</i>	

STYLE	7600	7650
WIDTHS	118" 300 cm	118" 300 cm
ROLL LENGTH	30 Linear Yards 27.4 Linear Meters	30 Linear Yards 27.4 Linear Meters
COMPOSITION	45% Polyester / 55% Acrylic Foamed Backing	100% Polyester
MESH WEIGHT	11.8 oz/yd ² 400 g/m ²	6.2 oz/yd ² 210 g/m ²
FABRIC THICKNESS	0.021 in 0.53 mm	0.017 in 0.43 mm
OPENNESS FACTOR	Opaque	Light-filtering
ACOUSTICAL VALUE	NRC .05 / SAA .07	NRC .40 / SAA .44

PHIFER
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403-1700 USA
Phone: 205.345.2120 • FAX: 205.391.0799
Toll Free USA/Canada: 1.800.221.5497
phifer.com • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.
™ UL, the UL logos and the UL mark are trademarks of UL LLC.
Photo courtesy of Hunter Douglas, South America.
© PHIFER INCORPORATED V21 052621 3036596